

SDT G2 Series

Dual-MPPT, Three-Phase



Technical Data	GW4K-DT	GW5K-DT	GW6K-DT	GW8K-DT	GW10KT-DT	GW12KT-DT	GW15KT-DT
PV String Input Data							
Max. DC Input Power (W)	6000	7500	9000	12000	15000	18000	22500
Max. DC Input Voltage (V)	1000	1000	1000	1000	1000	1000	1000
MPPT Range (V)	180~850	180~850	180~850	180~850	180~850	180~850	180~850
Start-up Voltage (V)	160	160	160	160	160	160	160
Min. Feed-in Voltage(V)	210	210	210	210	210	210	210
Nominal DC Input Voltage (V)	620	620	620	620	620	620	620
Max. Input Current (A)	12.5/12.5	12.5/12.5	12.5/12.5	12.5/12.5	12.5/12.5	12.5/25	12.5/25
Max. Short Current (A)	15.6/15.6	15.6/15.6	15.6/15.6	15.6/15.6	15.6/15.6	15.6/31.2	15.6/31.2
No. of MPP Trackers	2	2	2	2	2	2	2
No. of Input Strings Per MPP Tracker	1/1	1/1	1/1	1/1	1/1	1/2	1/2
AC Output Data							
Nominal Output Power (W)	4000	5000	6000	8000	10000	12000	15000
Max. Output Apparent Power (VA)	4400*1	5500*1	6600*1	8800*1	11000*1	14000*1	16500*1
Nominal Output Voltage (V)	400, 3L/N/PE						
Nominal Output Frequency (Hz)	50/60	50/60	50/60	50/60	50/60	50/60	50/60
Max. Output Current (A)	6.4	8	9.6	12.8	16	20.3	24
Output Power Factor	~1 (Adjustable from 0.8 leading to 0.8 lagging)						
Output THDi (@Nominal Output)	<3%	<3%	<3%	<3%	<3%	<3%	<3%
Efficiency							
Max. Efficiency	98.2%	98.2%	98.2%	98.2%	98.3%	98.3%	98.3%
European Efficiency	>97.6%	>97.6%	>97.6%	>97.6%	>97.7%	>97.7%	>97.7%
Protection							
Anti-Islanding Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Input Reverse Polarity Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Insulation Resistor Detection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
DC Surge Protection	Integrated (Type III)						
AC Surge Protection	Integrated (Type III)						
Residual Current Monitoring Unit	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Current Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Output Short Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
Output Over Voltage Protection	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated	Integrated
General Data							
Operating Temperature Range (°C)	-30~60	-30~60	-30~60	-30~60	-30~60	-30~60	-30~60
Relative Humidity	0~100%	0~100%	0~100%	0~100%	0~100%	0~100%	0~100%
Operating Altitude (m)	≤4000	≤4000	≤4000	≤4000	≤4000	≤4000	≤4000
Cooling	Natural Cooling	Natural Cooling	Natural Cooling	Fan Cooling	Fan Cooling	Fan Cooling	Fan Cooling
User Interface	LCD&LED						
Communication	WiFi or LAN or RS485						
Weight (kg)	15	15	15	16	16	18	18
Size (Width*Height*Depth mm)	354*433*147	354*433*147	354*433*147	354*433*155	354*433*155	354*433*155	354*433*155
Protection Degree	IP65	IP65	IP65	IP65	IP65	IP65	IP65
Night Self Consumption (W)	<1	<1	<1	<1	<1	<1	<1
Topology	Transformerless						

*1: For Belgium Max. Output Apparent Power (VA): GW4K-DT is 4000; GW5K-DT is 5000; GW6K-DT is 6000; GW8K-DT is 8000; GW10KT-DT is 10000; GW12KT-DT is 12000; GW15KT-DT is 15000.

*: Please visit GoodWe website for the latest certificates.



Distributeur: VDH Solar Groothandel B.V.

Finlandlaan 1, 2391 PV Hazerswoude-Dorp, Holland | +31 (0)172 235 990

VDH SOLAR info@vdh-solar.nl | www.vdh-solar.nl